

Doteck

Doteck R8 Series

8K H.265 UHD Video Encoder



Features

- (1) Standard 1U case, advanced CPU and GPU co-coding and transcoding technology are adopted
- (2) Web-based remote network management software
- (3) Support H.265/HEVC, H.264/AVC, AVS, AVS+, AVS2, AVS3(optional) encoding
- (4) Support MPEG-1 layer 2, MPEG-1 layer 3, LC-AAC, HE-AAC, AC3, EAC3 audio encoding format
- (5) Support three video acquisition methods: 4-channel 12G-SDI, or 4-channel

6G-SDI, or 4-channel 3G/HD/SD-SDI

- (6) Support 4320p, 2160p, 1080p, 1080i, 720p, 576i, 480i video input
- (7) Support SPTS, MPTS over UDP, FLV over RTMP, HLS over HTTP transmission stream IP input
- (8) Support UDP, RTP, RTSP, RTMP, HTTP, SRT network protocol output
- (9) Support the output video stream delay settings, delay time 0-120 seconds custom
- (10) Support internal multiplexer, which can multiplex SPTS program stream after multiplexing and transcoding into MPTS program stream
- (11) Support two gigabit ethernet ports, can be flexible configuration of IP program input and output physical channels
- (12) Support 10bit HDR
- (13) Support picture, caption overlay, multi-screen splicing and other software functions customization
- (14) Support main and standby signal switching function
- (15) Support GOP length, GOP structure and bit rate control buffer settings
- (16) Support CBR, VBR rate control mode
- (17) Stable operation of the equipment, supporting 7x24 hours uninterrupted work

Introduction

Dotek R8 series 8K H.265 UHD video encoder adopts standard 1U chassis structure, is a high quality broadcast audio and video real-time encoder transcoder product. This product not only has the traditional H.264/AVC video encoding and transcoding ability, but also supports the latest international video standard H.265/HEVC and China's independent intellectual property rights video standard AVS+, AVS, AVS2, AVS3 (optional) encoding format.

Dotek R8 series 8K H.265 UHD video encoder can compress 4-channel 12G-SDI, or 4-channel 6G-SDI, or 4-channel 3G/HD/SD-SDI digital video via powerful CPU+GPU cooperative coding module into any of the above mentioned video encoding formats in real time, and can also convert 1-channel 8K IP stream, or 4-channel 4K IP stream, or 16-channel HD IP stream or

32-channel SD IP stream in real time.

Technical Specifications

SDI input	
SDI signal format	12G/6G/3G/HD/SD-SDI
Channel	4-channel 12G-SDI, or 4-channel 6G-SDI, or 4-channel 3G/HD/SD-SDI
Resolution	4320p60/50 2160p60/50/30/25 1080p60/50/30/25 1080i60/50 720p60/50/30 576p25, 480p30 576i50, 480i60
Interface	BNC 75Ω
Video encoding	
Video encoding format	H.265/HEVC, H.264/AVC, AVS+, AVS, AVS2, AVS3(optional)
Bit rate	1.0Mbps-280.0Mbps
Rate control	CBR, VBR
Video pretreatment	De-interleaving
Audio encoding	
Audio encoding format	MPEG-1 layer 2, MPEG-1 layer 3, LC-AAC, HE-AAC, AC3, EAC3
Sampling rate	48KHz, 44.1KHz, 32KHz
Channel	Mono, stereo, 5.1, 7.1 surrounding stereo sound
Bit rate	64Kbps~1024Kbps
IP stream input	
Input interface	RJ45
Rate	1000Mbps
Stream encoding format	H.265/HEVC, H.264/AVC, AVS, AVS+, AVS2, AVS3(optional)
Network protocol	UDP, RTP, RTSP, RTMP, HTTP, SRT
Transport stream format	SPTS, MPTS, FLV, HLS
IP stream output	
Output interface	RJ45
Rate	1000Mbps
Stream encoding format	H.265/HEVC, H.264/AVC, AVS, AVS+, AVS2, AVS3(optional)
Network protocol	UDP, RTP, RTSP, RTMP, HTTP, SRT
Transport stream format	SPTS, MPTS, FLV, HLS
Control	
Management	Web-based remote network management software
Physical	

Dimension(H×W×D, mm)	44×433×636(mm)
Operation temperature	0-50℃
Relative humidity	0-95%, non-condensing
Power supply	130-260VAC, 50/60Hz

Doteck

Doteck Digital Technologies

Suite 819, Building C, Suite 11A, 11B, 11D, Tower 2, International Innovation Park, No. 2, Shangdi Info Road, Haidian District, BEIJING, CHINA, Postcode: 100085

Tel: +86-10-62120151

Mobile: +86-13910290608

Contact: LI XINJIAN

E-mail: Doteck@126.com

Welcome to visit our website for more info: www.Doteck.com